



Mini-out track 48v



Proiettore LED con adattatore meccanico con elettronica step-down 48v
150mA, gradi di emissione 26°. Orientabile 360° - 60°.

*LED projector with mechanical adaptor, with step-down 48v 150mA electronic,
emission degress 26°. Adjustability 360° - 60°.*

139.0078.00.-- 2 4 96

L=160mm 5,4W, 700Lm, CRI>90, 3000°K,

cod. 139.0078.00.2700.-- per 2700°K

cod. 139.0078.00.4000.-- per 4000°K



2 nero + adattatore nero
black + black adaptor

4 bianco + adattatore nero
white + black adaptor

96 bronzo + adattatore nero
bronzo + black adaptor

Mini-out track 48v DALI



Proiettore LED con adattatore meccanico con elettronica step-down 48v
150mA, gradi di emissione 26°. Orientabile 360° - 60°.

*LED projector with mechanical adaptor, with step-down 48v 150mA electronic,
emission degress 26°. Adjustability 360° - 60°.*

139.0078.00.03.-- 2 4 96

L=160mm 5,4W, 700Lm, CRI>90, 3000°K,

cod. 139.0078.00.03.2700.-- per 2700°K

cod. 139.0078.00.03.4000.-- per 4000°K

